

Temperature and humidity probe with 0-10V output

code: T0211



Humidity, temperature transmitter. Outdoor, indoor use.

Humidity, temperature probe on a cable. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio, specific enthalpy.

The device is supplied with T+RH probe with 1 meter cable.

NEW - AC Power - now also powered from 24 Vac !

Technical data

| | |
|---|--|
| TEMPERATURE SENSOR | |
| Measuring range | -30 to +105 °C |
| Accuracy | ±0.4 °C |
| Resolution | 0.1 °C |
| HUMIDITY SENSOR | |
| Measuring range | 0 to 100 % RH |
| Accuracy | ±2.5 % RH from 5 to 95 % at 23 °C |
| Resolution | 0.1% RH |
| DEW POINT | |
| Measuring range | -60 to +80 °C |
| Accuracy | ±1.5 °C at ambient temperature T <25 °C and RH >30 % |
| Resolution | 0.1 °C |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +80 °C |
| Channels | 1x connectable temperature+humidity probe |
| Counted values | dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy |
| Output | 0 - 10 V |
| Range of humidity sensor temperature compensation | all temperature range |
| Configuration of output | user adjustable from PC; measured range + value |
| Power | 15-30 Vdc; 24 Vac |
| Protection class | IP65 electronics; IP40 sensors |
| Dimensions | 88,5 x 145 x 39,5 mm; length/diameter of external probe 88/18 mm |
| External probe cable length | 1 meter |
| Weight | approx. 210 g |
| Warranty | 3 years |