

## Temperature probe Pt1000TR050M/M, MiniDin connector, cable 1 meter

code: SN270M

Temperature probe with Pt1000 sensor.

The temperature sensors Pt1000TR050M are designed for measuring temperatures of gaseous and liquid substances.



The temperature range for application of the sensor is -50°C to +400 °C, the maximum temperature may be exceeded up to 450°C in a short time (relates to active measuring part of sensor which is determined by spacer ring).

Around the lead in cable with Teflon insulation must not be temperature higher than 260 °C.

They meet the ingress protection IP64 according to the EN 60 529 standard. The sensors are suitable for temperature measurement in chemically non-aggressive environments, the using must be chosen with regard to temperature and chemical resistant housing and a cable.

### Technical data

TEMPERATURE SENSOR	
Measuring range	-50 to +400 °C, short-term +450 °C, maximum temperature around the cable and above the clamping ring is +260 °C
Accuracy	$\pm (0.15 + 0.002 t)$ at °C in range -50 to +250 °C  $\pm (0.3 + 0.005 t)$ at °C in range over +250 °C
Accuracy class	A
Time response	$t_{0.5} < 5$ s (in flowing water at $> 0.2$ m/s)
Type of sensing element	Pt1000
Temperature coefficient	3850 ppm / °C
GENERAL TECHNICAL DATA	
Wire connection	2-wire connection
Material of the case	stainless steel DIN 1.4301
Dimensions of the case	length 50 mm; diameter $6 \pm 0.1$ mm;   spacer ring diameter 8 mm
Lead-in cable	shielded teflon 2 x 0,22 mm <sup>2</sup>
Length of lead-in cable	1 meter
Connector	MiniDin
IP protection	IP64
Warranty	30 months