

## Web Sensor - remote thermometer hygrometer with Ethernet interface

code: T3510

Ambient temperature, relative humidity t-line Web sensor. Remote alarm. Web Sensor with built-in relative humidity and temperature sensors.



High precision capacitive polymer sensor ensures excellent long term calibration stability and ultimate accuracy. Dual line LCD is an advantage. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio and specific enthalpy.

### Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

### Technical data

TEMPERATURE SENSOR	
Measuring range	-30 to +80 °C
Accuracy	±0.6 °C
Resolution	0.1 °C
HUMIDITY SENSOR	
Measuring range	0 to 100 % RH
Accuracy	±2.5 % RH from 5 to 95 % at 23 °C
Resolution	0.1% RH
DEW POINT	
Measuring range	-60 to +80 °C
Accuracy	±1.5 °C at ambient temperature T <25 °C and RH >30 %
Resolution	0.1 °C
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +80 °C
Channels	internal temperature and humidity sensor
Counted values	dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy
Output	Ethernet
Range of humidity sensor temperature compensation	all temperature range
Measuring interval	2 s
Available temperature units	degrees Celsius, degrees Fahrenheit
Communication protocol	WWW, ModbusTCP, SNMPv1, SOAP, XML
Alarm protocols	E-mail, SNMP Trap, Syslog
Power	9-30 Vdc

Protection class	IP30
Dimensions	88,5 x 147,5 x 39,5 mm; stem length 75 mm
Weight	approx. 155 g
Warranty	3 years