

WebSensor - remote CO₂ concentration thermometer hygrometer with Ethernet interface

code: T6540



CO₂ concentration, temperature and relative humidity t-line Web sensor. Remote alarm.

Web Sensor with built-in CO₂ concentration, relative humidity and temperature sensors.

A multiple point CO₂ and temperature adjustment procedure leads to excellent CO₂ measurement accuracy over the entire temperature working range; this is a must for process control and outdoor applications. The dual wavelength NDIR CO₂ sensing procedure compensates automatically for ageing effects. The CO₂ module is highly resistant to pollution and offers maintenance free operation and outstanding long term stability.

High precision capacitive polymer sensor ensures excellent long term calibration stability and ultimate accuracy. Dual line LCD is an advantage. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio and specific enthalpy.

The CO₂ concentration is shown on the display or signaled by a color LED.

Processing and analysis of measured data:

- online in [COMET Cloud](#)
- [COMET Database](#) software
- [integration into 3-party systems](#)

Possibility to [extend the measuring range](#) for an additional charge:

- Measuring range: 0 to 10 000 ppm
- Accuracy: 100 ppm + 5% of the measured value at 25 °C and 1013 hPa

Technical data

| | |
|------------------------|---|
| TEMPERATURE SENSOR | |
| Measuring range | -30 to +80 °C |
| Accuracy | ±0.6 °C |
| Resolution | 0.1 °C |
| HUMIDITY SENSOR | |
| Measuring range | 5 to 95 % RH |
| Accuracy | ± 2,5 % RH |
| Resolution | 0.1% RH |
| DEW POINT | |
| Measuring range | -60 to +80 °C |
| Accuracy | ±1.6°C at ambient temperature T<25°C and RH>30% |
| Resolution | 0.1 °C |
| CO ₂ SENSOR | |

| | |
|---|--|
| Measuring range | 0 to 2000 ppm |
| Accuracy | ±(50ppm +2% from reading) at 25°C and 1013hPa |
| Resolution | 1 ppm |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +60 °C |
| Channels | internal temperature, humidity and CO ₂ sensor |
| Counted values | dew point, absolute humidity, specific humidity, mixing ratio, specific enthalpy |
| Output | Ethernet |
| Measuring interval | 2 s; CO ₂ 15 s |
| Range of humidity sensor temperature compensation | all temperature range |
| Communication protocol | WWW, ModbusTCP, SNMPv1, SOAP, XML |
| Alarm protocols | E-mail, SNMP Trap, Syslog |
| Power | 9-30 Vdc |
| Protection class | IP30 electronics, IP40 sensors |
| Dimensions | 88,5 x 170 x 39,5 mm; stem length 75 mm |
| Weight | approx. 150 g |
| Warranty | 3 years |